

Page 10, paragraph 14, delete the words “Figure 1 shows a side elevation view of a grader. A motive source 20 of the type known as a skidsteer loader comprising; an engine mounted within a chassis 24, a source of electrical generation, an operators compartment, a pair of front wheels 30, a pair of rear wheels, a variable speed direction control for the left side front and rear wheels, a second variable speed direction control for the right side front and rear wheels, a hydraulic power source, an auxiliary hydraulic control, and a hydraulic lifting mechanism with multiple pivot points, is shown with the grader attached to it.”. Further modify the same paragraph 14 by beginning the paragraph with the words –Figure 1 shows a side elevation view of a grader attached to a motive source 20 of the type known as a skidsteer loader. An engine is mounted within a chassis 24. a motive source of this type further includes a source of electrical generation and an operators compartment. A front wheel 30, or a surface contact propulsion assembly 21, on the left front section of the chassis, and another front wheel, or surface contact propulsion assembly, on the right front section of the chassis, are included on a motive source of this type. The aft section of the chassis includes a left side wheel or surface contact propulsion assembly and a right side wheel or surface contact propulsion assembly. The motive source further includes a means of bilateral propulsion control including a variable speed direction control for the left side front and rear wheels or surface contact propulsion assembly, and a variable speed direction control for the right side front and rear wheels or surface contact propulsion assembly. A hydraulic power source is included on the motive source. Also included are an auxiliary hydraulic control and a hydraulic lifting mechanism. The motive source is shown with the grader attached to it.--.

Page 11 paragraph 15, after the words “skidsteer which extends outward from”, delete the word “the” and add --a--. The next two words in the sentence are “forward end”, and then insert the number –27--.

At the end of paragraph 31 and after the words “The cutting edge is parallel to the rollers”, insert --, or depth guide axis,”--.